4











Use only original Graden blades from your Graden dealer for best resuts on your turf





CSI CONTOUR SAND INJECTION

ENGINE Honda 20hp v-twin unleaded petrol

key and recoil start

forward/reverse variable speed

front - 16 x 6.00-6 tube type rear - 9 x 3.5-4 tube type

CUTTING DEPTH variable from 0 to 1.5" (40mm)

CUTTING WIDTH 21" (525mm)

WIDTH 37" (950mm) LENGTH 50" (1250mm)

HEIGHT 48" (1220mm)

WEIGHT 640lbs (290kg)

SANDBOX CAPACITY 165lbs (75kg)

BLADES

standard blade width and spacing 17 x 5/64" (2mm) blades at 1 1/4" (30mm) spacing

optional blade widths 3/64" (1mm) and 1/8" (3mm)

optional variable spacing when not injecting sand tempered steel blades with eight tungsten tips

per blade blades fitted in reverse rotation to slice cleanly

deep scalloped design to prevent blades from becoming clogged

A floating head pedestrian Graden with the ability to faster than the GS04, it is ideal for level and undulating areas such as golf greens, approaches and lawns.







AUSTRALIAN DEALERS

through the turf

GOLF & BOWLING MACHINERY icrtoria el - Office (03) 9743 2400 obile - 0411 758 776 mail - info@golfandhowlin

